



CILINDRO DOPPIO EFFETTO SERIE XE 250 BAR

Velocità max. 0,5 m/s, pressione di picco max. 250 bar, pressione continua max. 140 bar, temperatura C°: - 25°C + 80°C.

| Ø D | Ø AL | Ø S | Corsa | Articolo | Z | C | E | L | L1 | Kg | Spinta A 100 Bar Kg | Tiro A 100 Bar Kg |
|-----|------------------|-----|-------|------------------|-----|------|------|----|----|------|------------------------|----------------------|
| 35 | 25 | 16 | 50 | XEA025BA016A0050 | 135 | 17 | 1/4" | 33 | 15 | 0,70 | 491 | 290 |
| | | | 100 | XEA025BA016A0100 | 185 | | | | | 0,95 | | |
| | | | 150 | XEA025BA016A0150 | 235 | | | | | 1,25 | | |
| | | | 200 | XEA025BA016A0200 | 285 | | | | | 1,50 | | |
| 42 | 32 | 20 | 50 | XEA032BA020A0050 | 155 | 16 | 1/4" | 33 | 20 | 1,30 | 804 | 490 |
| | | | 100 | XEA032BA020A0100 | 205 | | | | | 1,60 | | |
| | | | 150 | XEA032BA020A0150 | 255 | | | | | 1,95 | | |
| | | | 200 | XEA032BA020A0200 | 305 | | | | | 2,30 | | |
| | | | 250 | XEA032BA020A0250 | 355 | | | | | 2,70 | | |
| | | | 300 | XEA032BA020A0300 | 405 | | | | | 3,00 | | |
| | | | 400 | XEA032BA020A0400 | 505 | | | | | 3,70 | | |
| | | | 500 | XEA032BA020A0500 | 605 | | | | | 4,40 | | |
| 50 | 40 | 20 | 100 | XEA040BA020A0100 | 230 | 22 | 1/4" | 40 | 23 | 2,27 | 1.256 | 942 |
| | | | 150 | XEA040BA020A0150 | 280 | | | | | 2,67 | | |
| | | | 200 | XEA040BA020A0200 | 330 | | | | | 3,05 | | |
| | | | 250 | XEA040BA020A0250 | 380 | | | | | 3,45 | | |
| | | | 300 | XEA040BA020A0300 | 430 | | | | | 3,85 | | |
| | | | 350 | XEA040BA020A0350 | 480 | | | | | 4,27 | | |
| | | | 400 | XEA040BA020A0400 | 530 | | | | | 4,65 | | |
| | | | 450 | XEA040BA020A0450 | 580 | | | | | 5,08 | | |
| | | | 500 | XEA040BA020A0500 | 630 | | | | | 5,49 | | |
| | | | 50 | 40 | 25 | | | | | 100 | | |
| 150 | XEA040BA025A0150 | 280 | | | | 2,95 | | | | | | |
| 200 | XEA040BA025A0200 | 330 | | | | 3,39 | | | | | | |
| 250 | XEA040BA025A0250 | 380 | | | | 3,85 | | | | | | |
| 300 | XEA040BA025A0300 | 430 | | | | 4,32 | | | | | | |
| 350 | XEA040BA025A0350 | 480 | | | | 4,79 | | | | | | |
| 400 | XEA040BA025A0400 | 530 | | | | 5,26 | | | | | | |
| 450 | XEA040BA025A0450 | 580 | | | | 5,72 | | | | | | |
| 500 | XEA040BA025A0500 | 630 | | | | 6,20 | | | | | | |
| 550 | XEA040BA025A0550 | 680 | | | | 6,60 | | | | | | |
| 600 | XEA040BA025A0600 | 730 | | | | 7,13 | | | | | | |

N.B. A richiesta si costruiscono cilindri su specifiche del cliente.