



CILINDRO DOPPIO EFFETTO SERIE XE 250 BAR

Velocità max. 0,5 m/s, pressione di picco max. 250 bar, pressione continua max. 140 bar, temperatura C°: - 25°C + 80°C.

Ø D	Ø AL	Ø S	Corsa	Articolo	Z	C	E	L	L1	Kg	Spinta A 100 Bar Kg	Tiro A 100 Bar Kg
60	50	25	100	XEA050BA025A0100	240	22	3/8"	43	26	3,29	1.963	1.472
			150	XEA050BA025A0150	290					3,83		
			200	XEA050BA025A0200	340					4,34		
			250	XEA050BA025A0250	390					4,85		
			300	XEA050BA025A0300	440					5,35		
			350	XEA050BA025A0350	490					5,94		
			400	XEA050BA025A0400	540					6,40		
			450	XEA050BA025A0450	590					7,30		
			500	XEA050BA025A0500	640					7,43		
			550	XEA050BA025A0550	690					8,06		
			600	XEA050BA025A0600	740					8,46		
800	XEA050BA025A0800	940	10,71									
1000	XEA050BA025A1000	1140	12,87									
60	50	30	150	XEA050BA030A0150	290	22	3/8"	43	26	4,11	1.963	1.256
			200	XEA050BA030A0200	340					4,74		
			250	XEA050BA030A0250	390					5,35		
			300	XEA050BA030A0300	440					5,97		
			350	XEA050BA030A0350	490					6,55		
			400	XEA050BA030A0400	540					7,20		
			450	XEA050BA030A0450	590					7,80		
			500	XEA050BA030A0500	640					8,42		
			550	XEA050BA030A0550	690					9,04		
			600	XEA050BA030A0600	740					9,64		
			700	XEA050BA030A0700	840					10,85		
800	XEA050BA030A0800	940	12,10									
1000	XEA050BA030A1000	1140	14,57									

N.B. A richiesta si costruiscono cilindri su specifiche del cliente.