



CILINDRO DOPPIO EFFETTO SERIE XE 250 BAR

Velocità max. 0,5 m/s, pressione di picco max. 250 bar, pressione continua max. 140 bar, temperatura C°: - 25°C + 80°C.

Ø D	Ø AL	Ø S	Corsa	Articolo	Z	C	E	L	L1	Kg	Spinta A 100 Bar Kg	Tiro A 100 Bar Kg
80	70	35	100	XEA070BA035A0100	260	23	3/8"	50	33	6,09	3.847	2.885
			150	XEA070BA035A0150	310					6,95		
			200	XEA070BA035A0200	360					7,74		
			250	XEA070BA035A0250	410					8,60		
			300	XEA070BA035A0300	460					9,40		
			350	XEA070BA035A0350	510					10,26		
			400	XEA070BA035A0400	560					11,00		
			450	XEA070BA035A0450	610					11,88		
			500	XEA070BA035A0500	660					12,60		
			550	XEA070BA035A0550	710					13,66		
			600	XEA070BA035A0600	760					14,20		
800	XEA070BA035A0800	960	17,56									
1000	XEA070BA035A1000	1160	21,26									
80	70	40	200	XEA070BA040A0200	360	23	3/8"	50	33	8,28	3.847	2.591
			250	XEA070BA040A0250	410					9,26		
			300	XEA070BA040A0300	460					10,24		
			350	XEA070BA040A0350	510					11,20		
			400	XEA070BA040A0400	560					12,80		
			450	XEA070BA040A0450	610					13,11		
			500	XEA070BA040A0500	660					14,01		
			550	XEA070BA040A0550	710					15,10		
			600	XEA070BA040A0600	760					15,99		
			800	XEA070BA040A0800	960					19,73		
			1000	XEA070BA040A1000	1160					23,51		

N.B. A richiesta si costruiscono cilindri su specifiche del cliente.